


Adjustable Height Steel Tripod

Wallace Cranes offers steel adjustable portable tripods in 2-8 ton capacities. Most models are easily transportable and can be assembled/disassembled quickly making them an ideal choice for repair and maintenance jobs located off-site. In addition, our tripods are recommended to help set-up our larger cranes when a forklift or overhead lifting equipment is not available. All units include a standard base with lashing cable to prevent overspreading of the legs. Rubber Base Pad Kits, Mud Base Plate Kits, and Spike Base Kits are optional accessories available for every model.

Product Features

- Steel Construction
 - o Easily transportable
 - o Often used to help set-up our larger cranes when forklift or overhead lifting equipment is not available
- Available in 2, 3, 5, 6, 7 and 8 Ton capacities
- Adjustable heights available from 4'11" to 18'3"
- Spring loaded bolts permit tripod height adjustments they can be locked out until desired height is reached, then unlocked to engage automatically
- · Machined alloy head holds free swiveling eye-bolt which always hangs plumb
- · Legs rest securely on standard bases optional base accessories available for different surfaces
- · Lashing kit provides an extra precaution against slipping and can be used with all of the optional base accessories



Click to enlarge

Heights under eyebolt are figured for optimum strength

(C) not exceeding 75% of adjusted (B).

Crane Sizes and Model Numbers

| | | A | | В | | C | | | |
|---------------------|-----------------|-------------------------------|---------|-------------------|--------|--------------------------|------|------------|----------------------------|
| Maximum Capacity | Model Number | Height - Eye Bolt to Floor | | Overall Length | | Distance Between Legs | | Net Wt. | Spike Base Model Number |
| | | Max. | Min. | Max. | Min. | Max. | Min. | ** | Number |
| 2 Ton | R3-4121 | 16' 3" | 10' 10" | 18' 9" | 12' 9" | 165" | 93" | 225 | 676 |
| 3 Ton | R3-6101 | 13' 7" | 9' 1" | 15' 9" | 10' 9" | 138" | 78" | 189 | 676 |
| 5 Ton | R3-1081 | 10' 10" | 7' 1" | 12' 9" | 8' 9" | 111" | 63" | 160 | 676 |
| 6 Ton | R3-1261 | 8' 2" | 5' 6" | 9' 9" | 6' 9" | 84" | 48" | 136 | 676 |
| | H3-12141 | 18' 3" | 12' 0" | 21' 9" | 14' 9" | 192" | 108" | 411 | 1514 |
| 7 Ton | H3-1481 | 10' 3" | 6' 8" | 12' 9" | 8' 9" | 111" | 63" | 253 | 1514 |
| | H3-14121 | 15' 7" | 10' 3" | 18' 9" | 12' 9" | 165" | 93" | 453 | 1514 |
| 8 Ton | H3-1661 | 7' 6" | 4' 11" | 9' 9" | 6' 9" | 84" | 48" | 210 | 1514 |
| | H3-16101 | 12' 11" | 8' 5" | 15' 9" | 10' 9" | 138" | 78" | 385 | 1514 |

Note: Maximum capacity is in thousands of pounds. Capacities derated at no additional charge. Simply change number in red to require capacity accordingly when ordering.