




## WALLACE CRANES PORTABLE CRANE CANTILEVER CHART

GANTRY MODEL NUMBER: 3T24-S10AC  
 I-BEAM: S8"X18.4#/'X10'  
 I-BEAM LENGTH (OVERALL SPAN): 120 Inches  
 MAXIMUM CANTILEVER DISTANCE (A): 30 Inches  
 GANTRY RATED CAPACITY: 6,000 Lbs.  
 MAXIMUM CANTILEVERED LOAD (B): 3600 Lbs.  
 GANTRY WEIGHT: 2005 Lbs.  
 I-BEAM WEIGHT: 184 Lbs.



**PROPER CANTILEVER PROCEDURES**  
 Required counterweight should not be supported by gantry caster frame.

Load and trolley should be able to freely traverse the I-beam through the main legs and brace legs of the gantry.

### REQUIRED COUNTERWEIGHT AT [C]

A	B	B	B	B	B	B	B	B	B
IN	400	800	1200	1600	2000	2400	2800	3200	3600
FEET	LBS.	LBS.	LBS.	LBS.	LBS.	LBS.	LBS.	LBS.	LBS.
1	0	0	0	0	0	0	0	0	0
2	0	0	0	0	20	220	420	620	820
2.5	0	0	0	94	361	628	894	1161	1428