



## WALLACE CRANES PORTABLE CRANE CANTILEVER CHART

GANTRY MODEL NUMBER: FHS611-M35AC  
 I-BEAM: S18" X 54.7#/' X 35' REINF 10" X 12'  
 I-BEAM LENGTH (OVERALL SPAN): 420 Inches  
 MAXIMUM CANTILEVER DISTANCE (A): 105 Inches  
 GANTRY RATED CAPACITY: 6000 Lbs.  
 MAXIMUM CANTILEVERED LOAD (B): 3600 Lbs.  
 GANTRY WEIGHT: 2937 Lbs.  
 I-BEAM WEIGHT: 2220 Lbs.



**PROPER CANTILEVER PROCEDURES**  
 Required counterweight should not be supported by gantry caster frame.

Load and trolley should be able to freely traverse the I-beam through the main legs and brace legs of the gantry.

REQUIRED COUNTERWEIGHT AT [C]

A IN FEET	B 400 LBS.	B 800 LBS.	B 1200 LBS.	B 1600 LBS.	B 2000 LBS.	B 2400 LBS.	B 2800 LBS.	B 3200 LBS.	B 3600 LBS.
1	0	0	0	0	0	0	0	0	0
2	0	0	0	0	0	0	0	0	0
3	0	0	0	0	0	0	0	0	0
4	0	0	0	0	0	0	0	0	0
5	0	0	0	0	0	0	0	0	0
6	0	0	0	0	0	0	0	85	250
7	0	0	0	0	0	9	209	409	609
8	0	0	0	0	45	282	519	756	993
8.75	0	0	0	0	234	501	768	1034	1301